

Amendments to the Claims

Please amend Claims 1 and 20.

Listing of Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Claim 1 (currently amended): A seat anchorable to the floor of a vehicle, comprising:

a seat cushion comprising a forward portion, a rearward portion, a top portion, a bottom portion and a first frame;

a forward support leg pivotably coupled to the bottom portion of the seat cushion proximate the forward portion and adapted to contact the floor of the vehicle when the seat cushion is generally horizontal;

an anchor member having a single seat cushion pivot coupled between the seat cushion and a structural portion of the vehicle floor such that the seat cushion is pivotable about the rearward portion;

a seatback comprising an upper portion, a lower portion and a second frame, wherein the second frame is pivotably coupled to the anchor member proximate the lower portion of the seatback; and

a moveable headrest coupled to the upper portion of the seatback,
wherein the seatback is positionable to the orientation of the seat cushion, and
wherein the forward support leg automatically folds into a stowed position proximate the bottom portion of the seat cushion when the seat cushion is pivoted upwardly, and automatically unfolds into an extended position generally perpendicular to the seat cushion when the seat cushion is pivoted downwardly.

Claim 2 (original): The seat of claim 1 wherein the seat cushion is upwardly pivotable to a generally vertical position proximate and facially adjacent the seatback.

Claim 3 (original): The seat of claim 1 wherein the seatback is downwardly pivotable to a generally horizontal position proximate and facially adjacent the seat cushion.

Claim 4 (original): The seat of claim 1 wherein the headrest is pivotably coupled to the seatback.

Claim 5 (canceled)

Claim 6 (original): The seat of claim 1 wherein the seat cushion is releaseably retained in at least one position by a first latch, and wherein the first latch may be actuated by a first lever to release the first latch when the seat cushion is to be pivoted.

Claim 7 (original): The seat of claim 6 wherein the seat cushion is releaseably retained either in a first generally horizontal position or a second generally vertical position.

Claim 8 (original): The seat of claim 1 wherein the seatback is releaseably retained in at least one position by a second latch, and wherein the second latch may be actuated by a second lever to release the second latch when the seatback is to be pivoted.

Claim 9 (original): The seat of claim 8 wherein the seatback is releaseably retained in either a first generally vertical position or a second generally horizontal position.

Claim 10 (original): The seat of claim 1 wherein the headrest is releaseably retained in at least one position by a third latch, and wherein the third latch may be actuated by a third lever to release the third latch when the headrest is to be pivoted.

Claim 11 (original): The seat of claim 10 wherein the headrest is releasably retained in either a first extended position generally aligned with the seatback or a second stowed position generally perpendicular to the seatback.

Claim 12 (original): The seat of claim 1 wherein the seat cushion, seatback and headrest each provide a visual indication when not in a retained condition.

Claim 13 (previously presented): The seat of claim 1, wherein the headrest is linked to the seatback such that the headrest advances toward a stowed position as the seatback is downwardly pivoted, and wherein the headrest advances toward an extended position as the seatback is upwardly pivoted.

Claim 14 (previously presented): The seat of claim 1, wherein the headrest is biased toward a stowed position and releasably retained in an extended position.

Claim 15 (previously presented): The seat of claim 1, wherein at least one passenger is deterred from utilizing the seat when the headrest is not in an extended position.

Claim 16 (canceled)

Claim 17 (canceled)

Claim 18 (canceled)

Claim 19 (canceled)

Claim 20 (currently amended): A seat anchorable to the floor of a vehicle, comprising:

a seat cushion comprising a forward portion, a rearward portion, a top portion, a bottom portion and a first frame, wherein the seat cushion is releasably retained in at least

one position by a first latch, and wherein the first latch may be actuated by a first lever to release the first latch when the seat cushion is to be pivoted;

a forward support leg pivotably coupled to the bottom portion of the seat cushion proximate the forward portion and adapted to contact the floor of the vehicle when the seat cushion is generally horizontal, and wherein the forward support leg automatically folds to a stowed position proximate the bottom portion of the seat cushion when the seat cushion is upwardly pivoted, and wherein the forward support leg automatically unfolds to an extended position generally perpendicular to the seat cushion as the seat cushion is downwardly pivoted;

an anchor member having a single seat cushion pivot coupled between the seat cushion and a structural portion of the vehicle floor such that the seat cushion is pivotable about the rearward portion;

a seatback comprising an upper portion, a lower portion and a second frame, wherein the second frame is pivotably coupled to the anchor member proximate the lower portion of the seatback, and wherein the seatback is releasably retained in at least one position by a second latch, and wherein the second latch may be actuated by a second lever to release the second latch when the seatback is to be pivoted; and

a moveable headrest coupled to the upper portion of the seatback, wherein the headrest is releasably retained in at least one position by a third latch, and wherein the third latch may be actuated by a third lever to release the third latch when the headrest is to be pivoted,

wherein the seatback is positionable to the orientation of the seat cushion, and

wherein the forward support leg automatically folds into a stowed position proximate the bottom portion of the seat cushion when the seat cushion is pivoted upwardly, and automatically unfolds into an extended position generally perpendicular to the seat cushion when the seat cushion is pivoted downwardly.